



Fixing Centres 145mm

- Central Battery Hold off Driver
- Suitable for 50V, 110V & 240V Systems
- Runs at 350mA or 700mA - (Selected via Jumper)
- Operates from AC or DC Systems
- Available in Remote Enclosure if Required

The CBH range is supplied either as a driver for integrally mounting within the luminaire or can be housed in a remote enclosure for remote mounting. It is also suitable for powering our range of dedicated emergency LEDs.

The CBH unit is designed as a central battery slave (240V, 110V or 50V AC/DC) to run a dedicated LED in emergency, with the output held off whenever the 240V AC unswitched supply is present.

At the point the unswitched supply is broken, the driver will accept the feed from the central battery and power either one two or three LEDs in series at either 350mA or 700mA.

50V AC or DC	1 LED at 350mA or 700mA (2.5V-3.5V)
110V AC or DC	1-3 LEDs in series at 350mA or 700mA (2.5V-10V)
240V AC or DC	1-3 LEDs in series at 350mA or 700mA (2.5V-10V)

There is 1 version available -

Order Codes

CBH-M	Hold off Driver to run 1No. 350mA or 700mA LED from 50V AC or DC Central Battery System or 1-3 LEDs in series from either 110V or 240V AC or DC Central Battery Systems.
--------------	--

Technical Details:

Emergency Voltage from CBU	45-240V AC/DC (50V, 110V & 230V Nominal)
Emergency Power from CBU	See Installation Instruction
Mains Un-Switched Supply	230-240V AC 50/60Hz
240V Hold off Current/Power	6mA, 1W, $\lambda = 0.65$
Dimensions L x W x H	152mm x 26.5mm x 28.5mm (f/c 145mm)
Module Weight	0.15Kg
Terminal Cable Size	0.5 - 1.5mm ² Push Fit